



RG213 and RG214 Cable Sets are suitable for operation from DC~6 GHz. These cable sets conform to MIL -C-17.

APPLICATIONS (DC~6 GHz)

- General purpose test applications
- MIL spec interconnect applications
- Environmental and chamber testing

MIL STANDARDS CONFORMANCE

- MIL-C-17 conformant Cable
- MIL-PRF-39012 conformant Connectors

Physical & Mechanical Specifications

Parameter	RG213	RG214
Inner Conductor	Copper wire (stranded)	Silver Plated Copper (stranded)
Dielectric	Polyethylene	Polyethylene
Shield 1	Copper Braid	Silver Plated Copper Braid
Shield 2	-	Silver Plated Copper Braid
Jacket	Black PVC, 10.3mm	Black PVC, 10.8mm
Temperature range	-55°C ~ +85°C	-40°C ~ +85°C
Weight	0.162 Kg/m	0.205 Kg/m

Electrical Specifications

Parameter	RG213	RG214
Impedance	50Ω	50Ω
Frequency	DC~6 GHz	DC~6 GHz
Capacitance	101 pF/meter (30.79pF/feet)	100 pF/meter (30.48pF/feet)
Velocity of Propagation	66%	66%


Attenuation Vs Frequency (dB/100 meter)

Frequency (MHz)	50	100	400	600	1000	1200	1500	2000	3000
RG-213	4.3	6.5	14.6	18.5	25	28	32	39	49
RG-214	5.2	7.7	16.9	21	28	31	36	43	54


Shown trademarks are property of their respective owners.

While the information contained herein in this catalog, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.

**Return Loss Plots of RG214 Cable Assembly
2 meter long with N(Male) to TNC (Male) Straight Connectors**



**Insertion Loss Plots of RG214 Cable Assembly
2 meter long with N(Male) to TNC (Male) Straight Connectors**



Shown trademarks are property of their respective owners.

While the information contained herein in this catalog, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.

Connector Specifications

Specifications	N Connectors	TNC Connectors
Outer Conductor	Brass, Nickel alloy plated	Brass, Nickel alloy plated
Center Conductor	Brass, Gold Plated	Brass, Gold Plated
Insulation	PTFE	PTFE
Gasket	Silicon Rubber	Silicon Rubber
Nominal Impedance	50 Ω	50Ω
Frequency range	DC~6 GHz	DC~6 GHz
Mating/Unmating	500 operations min.	500 operations min.

Ordering Codes Description

RG213/RG214 - □ □ - □ (□ / □) - □ (□ / □) - □
L L 1 2 3 1 2 3 U

LL	Length	0.5 = 0.5 ; 1 = 1.0 ; 2 = 2.0
1	Connector Series	SMA = SMA ; N = N ; BNC = BNC; TNC = TNC
2	Male/Female Designator	M = Male ; F = Female
3	Orientation of Connector	ST = Straight ; RA = Right Angle
U	Unit of Length	M = Meter ; F = Feet

1 meter RG214 cable set with SMA (Male) on both sides = RG214-1.0-SMA(M/ST)-SMA(M/ST)-M

Cable Set Ordering Codes

Ordering Code	Length	Insertion Loss (dB) Typical						
		100 MHz	400 MHz	1 GHz	1.5 GHz	3 GHz	4 GHz	6 GHz
N (Male) Straight - N (Male) Straight (DC~6 GHz)								
RG214-1.0-N(M/ST)-N(M/ST)-M	1m	0.1	0.209	0.345	0.434	0.651	0.774	0.993
RG214-5.0-N(M/ST)-N(M/ST)-M	5m	0.366	0.774	1.50	1.84	2.90	3.20	4.20
RG214-1.0-N(M/ST)-N(M/ST)-F	1 feet	0.054	0.111	0.18	0.224	0.327	0.385	0.485
RG214-2.0-N(M/ST)-N(M/ST)-F	2 feet	0.074	0.154	0.252	0.316	0.469	0.555	0.708
TNC (Male) Straight - TNC (Male) Straight (DC~4 GHz)								
RG214-1.0-TNC(M/ST)-TNC(M/ST)-M	1m	0.107	0.222	0.367	0.461	0.688	0.816	-
RG214-5.0-TNC(M/ST)-TNC(M/ST)-M	5m	0.373	0.787	1.52	1.86	2.92	3.24	-
RG214-1.0-TNC(M/ST)-TNC(M/ST)-F	1 feet	0.061	0.124	0.201	0.25	0.364	0.427	-
RG214-2.0-TNC(M/ST)-TNC(M/ST)-F	2 feet	0.081	0.167	0.274	0.342	0.506	0.598	-
TNC (Male) Straight -N (Male) Straight (DC~4 GHz)								
RG214-1.0-TNC(M/ST)-N(M/ST)-M	1m	0.104	0.216	0.356	0.448	0.669	0.795	-
RG214-5.0-TNC(M/ST)-N(M/ST)-M	5m	0.37	0.78	1.54	1.88	2.94	3.28	-
RG214-1.0-TNC(M/ST)-N(M/ST)-F	1 feet	0.057	0.117	0.19	0.237	0.346	0.406	-
RG214-2.0-TNC(M/ST)-N(M/ST)-F	2 feet	0.078	0.161	0.263	0.329	0.488	0.577	-

Shown trademarks are property of their respective owners.

While the information contained herein in this catalog, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.