

P1

Connector	Cable	Average Power (Watt)	Frequency (GHz)
SMA, BMA, QMA	on cables MF02, SF02, semirigid 0.141 on cables MF05, SF05, semirigid 0.085 on cables ULL04, ULL05, HFH18	70 25 110	18
TNC	on cables RG142, 223, 400, 214 on cables ULL04 on cables ULL05 on cables MF02, SF02, semirigid 0.141 on cables MF05, SF05, semirigid 0.085	350 140 200 70 25	11
TNC 18 GHz	on cable ULL05 on cable HGH18G	150 170	18
N	on cables RG142, 223, 400, 214 on cables ULL04 on cables ULL05 on cables MF02, SF02, semirigid 0.141 on cables MF05, SF05, semirigid 0.085	350 140 200 70 25	11
N 18 GHz	on cable ULL05 on cable HFH18G	150 170	18
MCX	right-angle on cable RG178 straight on cable RG178 right-angle on cable RG316, RG174	100 150 200	<1
SMB	right-angle on cable RG178 straight on cable RG316, RG174 right-angle on cable RG316, RG174	100 150 200	<1
QMA	on cable RG316, RG142, 223, 400	150	2.5
HN	right-angle on cable RG142, 223, 400, 214	350	2.5

Shown trademarks are property of their respective owners.

While the information contained herein in this catalog, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.